



## MODEL SELECTION

2000W / 19-72 VDC INPUT		
MODEL NUMBER	VOLTAGE	CURRENT
NTDC-2000L-12	12 V	120 A
NTDC-2000L-24	24 V	80 A
NTDC-2000L-28	28 V	71 A
NTDC-2000L-48	48 V	41 A

2000W / 72-144 VDC INPUT		
MODEL NUMBER	VOLTAGE	CURRENT
NTDC-2000H-12	12 V	120 A
NTDC-2000H-24	24 V	80 A
NTDC-2000H-28	28 V	71 A
NTDC-2000H-48	48 V	41 A

3000W / 19-72 VDC INPUT		
MODEL NUMBER	VOLTAGE	CURRENT
NTDC-3000L-12	12 V	180 A
NTDC-3000L-24	24 V	125 A
NTDC-3000L-28	28 V <td 107 A	
NTDC-3000L-48	48 V	62 A

3000W / 72-144 VDC INPUT		
MODEL NUMBER	VOLTAGE	CURRENT
NTDC-3000H-12	12 V	180 A
NTDC-3000H-24	24 V	125 A
NTDC-3000H-28	28 V	107 A
NTDC-3000H-48	48 V	62 A

## OPTIONAL DESIGNATIONS

- HSP	Hot Swap
- ORD	Redundant Operation
- CC	Conformal Coating
- MIL	Ruggedized / Militarized

- PNL	Panel Mount
- RK	Rack Mount
- PAR	Parallel Operation

## MECHANICAL OUTLINE

